

RTS-1, Personal bioreactor



DESCRIPTION

RTS-1 is personal bioreactor which utilize patented Reverse-Spin® technology that applies non-invasive, mechanically driven, low energy consumption, innovative type of agitation where cell suspension is mixed by the singleuse falcon bioreactor tube rotation around its axis with a change of direction of rotation motion resulting in highly efficient mixing and oxygenation for aerobic cultivation. Combined with a near-infrared optical system it is possible to register cell growth kinetics non-invasively in real time.



- Reverse–Spin® mixing principle in 50 ml falcon tubes allows to achieve high k_{a} (h^{-1}) up to 450 which is essential for efficient aerobic cultivation
- Individually controlled bioreactor accelerates optimization process
- Possibility to cultivate microaerophilic and obligate anaerobic microorganisms (not strict anaerobic conditions)
- Reverse–Spin® mixing principle enables non-invasive biomass measurement in real time
- Near-infrared optical system makes it possible to register cell growth kinetics
- Free of charge software for storage, demonstration and analysis of data in real time
- Compact design with low profile and small footprint for personal application
- Temperature control for bioprocess applications
- Active cooling for rapid temperature control, e.g. for temperature fluctuation experiments
- Task profiling for process automatization
- Cloud data storage to remotely monitor the process of cultivation while at home or using a mobile phone

Software features:

- Real–Time cell growth logging
- 3D graphical representation of OD or growth rate over time over unit
- Pause option
- Save/Load option
- Report option: PDF and Excel
- Connect up to 12 units (recommended) simultaneously to 1 computer
- Remote monitoring option (requires internet connection)
- Cycling/Profiling options
- User manual calibration possibility for most cells

Typical applications:

- Fermentation real time growth kinetics
- Clone candidate screening
- Protein expression
- Temperature stress and fluctuation experiments
- Media screening and optimization
- Growth characterization
- Inhibition and toxicity tests
- Strain quality control


CAT. NUMBER

BS-010158-A04	230VAC 50/60Hz Euro plug
BS-010158-A05	230VAC 50/60Hz UK plug
BS-010158-A03	230VAC 50/60Hz AU plug
BS-010158-A02	100VAC 50/60Hz US plug, 120VAC 60Hz US plug


SPECIFICATIONS

Measurement range	0–10 OD at 10–20ml volume (0–19 OD λ 600 nm equivalent) 0–8 OD at 20–30ml volume (0–15.2 OD λ 600 nm equivalent)
Measurement precision	\pm 0.3 OD
Light source	NIR Light diode
Measurement wavelength (λ)	850 nm
Measurement periodicity per hour	1–60
Cultural media volume	5–30 ml
Temperature setting range	+25°C ... +70°C
Temperature control range	5°C above ambient ... +70°C
Temperature stability	\pm 0.1°C
Display	LCD
Speed control range	50–2,000 rpm
Max. number of units connected to the software	12
Type of tube for aerobic cultivation	50 ml tube with membrane filter (TubeSpin® Bioreactor 50, TPP®)*
Type of tube for anaerobic cultivation	50 ml tube with membrane filter (TubeSpin® Bioreactor 50, TPP®)* * — it is also possible to use other manufacturer tubes of the same type, e.g. Corning® 50ml Mini Bioreactor, but the device rotor must be modified. It is possible to request this modif.
Minimum PC requirements	Intel/AMD Processor, 1 GB RAM Windows XP*/Vista/7/8/8.1/10, USB 2.0 port
Optimal PC requirements	Intel/AMD Processor, 3 GB RAM Windows XP*/Vista/7/8/8.1/10, USB 2.0 port * not guaranteed because OS not supported by producer
Overall dimensions (W×D×H)	130 × 212 × 200 mm
Weight	1.7 kg
Input current/power consumption	12 V DC, 3.3 A / 40 W
External power supply	Input AC 100–240 V 50/60 Hz, Output DC 12 V

ACCESSORIES




USB 2.0 Hub 10 × ports
BS-010158-BK



TubeSpin® Bioreactor 50 - 20
BS-010158-AK

50 ml tubes with membrane
filter TubeSpin® Bioreactor
50, TPP® 20 pcs.



TubeSpin® Bioreactor 50 - 180
BS-010158-CK

50 ml tubes with membrane
filter TubeSpin® Bioreactor
50, TPP® 180 pcs.